

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 11322305 A

(43) Date of publication of application: 24.11.1999

(51) Int. Cl. C01B 13/11
H01T 23/00(21) Application number: 10158400
(22) Date of filing: 21.05.1998

(71) Applicant: ICHIKAWA MASAHIKE

(72) Inventor: ICHIKAWA MASAHIKE

(54) OZONE GENERATION METHOD AND OZONE GENERATOR


spirally wound electrically conductive material is used as the 2nd electrode.

COPYRIGHT: (C)1999 JPO

(57) Abstract

PROBLEM TO BE SOLVED: To provide an ozone generation method and an ozone generator generating a large amount of ozone with a small-sized apparatus.

SOLUTION: A 1st electrode 13 is sealed or embedded in a dielectric material 12, a 2nd electrode 15 is placed in contact with or near the outer surface of the dielectric material and a high voltage is applied to the 1st and the 2nd electrodes. The dielectric material 12 is formed in the form of a cylinder, the 1st electrode 13 is sealed or embedded in the dielectric material, and the 2nd electrode 15 is spirally wound around the outer circumference of the cylindrical dielectric material. A



BEST AVAILABLE COPY